BONDPROOF - DPH

(Dustproofer & Floor Hardner)

Page 1/3.

BONDPROOF-DPH is an aqueous chemical treatment in concentrate form designed to improve both old and new concrete floor finishes. It combines easily with water for application purposes ensuring that a dense, hard, dust free surface is provided.

ADVANTAGES

- Oil and grease proof.
- Wear and abrasion resistance improved.
- Economical and easily applied by unskilled labour.
- Dustproofs and reduces permeability to liquids.
- Can be used on floors cured with BONDCURE concrete curing liquid.

SURFACE PREPARATION

All surfaces must be clean and free of oil, grease and other chemical contamination. Oil and grease can be removed using a Heavy Duty Degreaser. Any dry dust should be removed by vacuum cleaning or brushing. New concrete will require at least 10 days to thoroughly dry out before treatment.

APPLICATION

Using the dilution rates shown overleaf **BONDPROOF-DPH** should be applied by watering can and spread over the surface with a brush or squeegee and kept moving until absorption is no longer evident. Any excess solution should be drained off to leave a dry surface. Second and third coats should be applied after each previous treatment is thoroughly dry (24 hours is usually long enough). Following the final treatment the surface should be washed with water to remove any solution which has not been absorbed. This should normally be done 12-24 hours after the final application but in hot weather should be done earlier. Clean all equipment with water immediately after use. Contact with glass, metal, paintwork or clothing should be avoided.

BONDPROOF - DPH

(Dustproofer & Floor Hardner)

Page 2 / 3.

TYPICAL PROPERTIES

Colour : Clear
 Minimum Overcoating Time : 24 Hours
 Shelf Life : 1 Year

COVERAGE & DILUTION RATES

Surface Quality	Coverage m ² / Ltr of undiluted BONDPROOF-DPH for Complete Treatment.	Aplication Coats	Dilution Ratio By Volume BONDPROOF- DPH To Water
Porous to Mod. Dense	3.5 to 5.5	3	1:4 1st Coat 1:3 2nd Coat 1:2 3rd Coat
Dense	6 to 8	2	1:4 1 st Coat 1:3 2 nd Coat
Terrazzo	15 to 25	1	1:5 Single Coat

STORAGE

BONDPROOF-DPH should not be allowed to freeze and must be kept out of the reach of children.

PACKAGING

BONDPROOF-DPH is supplied in 5 litre, 25 litre and 205 litre units.

LIMITATIONS

If the treated surface is to receive a subsequent coating we recommend that a test patch be prepared before total treatment to check adhesion.

BONDPROOF - DPH

(Dustproofer & Floor Hardner)

Page 3 / 3.

HEALTH & SAFETY PRECAUTIONS

Goggles, rubber gloves and boots should be used during application. Contact with the skin should be avoided. Accidental splashes on the skin should be washed off with soap and water. Contact with the eyes should be avoided however should accidental contact occur the eyes should be washed with copious amounts of water and medical treatment sought. If swallowed do not induce vomiting but seek medical aid. Contaminated clothing should be removed.

General Note:

This leaflet is a guide for the use of the product concerned. Whilst the information and / or specification given are to the best of our knowledge true, accurate and in accordance with latest technical developments, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors as the conditions of use, method of application and any labour involved are beyond our control.

* * * * *

BondChem@NewYork.USA.com www.Bond-Chem.com