

GYPBOND

**High Quality All Purpose Environmentally Friendly Joint Compound
Ready Mixed / Non-Asbestos.**

GYPBOND is an all purpose chemically engineered ready to use putty for application on gypsum boards and wooden surfaces. GYPBOND is specially formulated for the painter to fill joints between gypsum boards and also hairline cracks in interior surfaces. On drying, it gives a high quality smooth surface prior to painting. When fully dry, GYPBOND bonds extremely well with the substrate and due to its high adhesion does not flake off. It is recommended to apply a glass fibre mesh cloth as reinforcement in between the joints.

Uses

- Putty for gypsum board joints
- Putty for filling gaps and cracks
- Skim coat on plaster before painting
- All levels of dry wall finishing.

Surface Preparation

Surfaces should be sound, clean and free from dust, dirt and foreign matter. Any ridges and traces of oil should be removed. There should not be any fixed movement between the joints. Gypsum boards must be fixed properly with screws.

Application

Using a putty knife or trowel, apply GYPBOND in a thin even layer and embed a glass fibre mesh. Lightly press the mesh to ensure it is fully embedded. Then apply a 2nd layer of GYPBOND and completely smoothen the surface using putty knife or trowel.

Coverage

15-20 sq. meter per 28 kg pail for 1mm thickness.

Packing

28 kgs. pails.

* * * * *